



### THRIVE™ FULL SYNTHETIC UNIVERSAL ATF

#### Description

**THRIVE™** Full Synthetic Universal ATF provides an innovative, versatile solution to virtually all your ATF needs. This advanced performance Full Synthetic ATF is specifically designed as a universal solution for modern automatic transmissions. Its state-of-the-art additive system provides optimum shear stability, oxidation resistance and durability delivering ultimate protection and peak performance in passenger cars, SUVs, and light trucks.

**THRIVE™** Full Synthetic Universal ATF meets the strictest OEM specifications in low and high viscosity applications and is recommended where the following specifications are required: DEXRON VI, DEXRON III/III(H)/IIE, DEXRON II, MERCON LV, Hyundai/KIA SP-II/III/IV, Toyota WS/T-III/T-IV, Mercedes, Honda Z-1, Allison and Nissan Matic Fluids. Our fluid is also suitable for use in MERCON V\* specifications. See table on reverse side for a comprehensive listing of 'suitable for use in' applications.

**THRIVE™** Full Synthetic Universal ATF is compatible with traditional fluids whether used in a complete fluid change or vehicle top-off.

\* Not for use in extended drain heavy duty, Continuous Variable Transmissions (CVT), Dual Clutch Transmissions (DCT) or Ford Type F applications.

\* Please note that legislation in California prohibits recommending this fluid in certain applications where the viscometrics do not match those of the official OEM specification. Therefore we do not recommend the use of THRIVE Universal ATF in these applications in California.



#### Features/Benefits

- ✓ **Universal ATF**  
Simplifies and consolidates inventories, reduces inventory investment
- ✓ **Excellent Oxidation Stability**  
Superior and longer lasting high temperature protection, less sludge and improved wear protection
- ✓ **High Shear Stability**  
Retains its excellent friction characteristics longer and across a wide temperature range providing smooth shifting and wear protection over extended service intervals
- ✓ **Improved protection against pitting**
- ✓ **Lower Foaming**

#### Typical Properties

<b>Product Number</b>	<b>298</b>
Kinematic Viscosity D-445 @ 40°C, cSt	29.1
Kinematic Viscosity D-445 @ 100°C, cSt	5.9
Viscosity Index	153
Brookfield Viscosity D-2893 cPat -40°C	10,000
Appearance	Red



## THRIVE™ FULL SYNTHETIC UNIVERSAL ATF

Suitable for use in the following applications:

GM Dexron® -VI	Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309	Porsche ATF 3403-M115
Ford MERCON® LV	Fuso ATF-II/SPIII/A4	Porsche T-IV (JWS 3309)
Acura ATF-Z1	GM9986195 (Aisin AW, JWS 3309)	Saab T-IV (JWS 3309)
AISIN WARNER JWS 3309, JWS 3324, T IV, AW-1	GM TASA	Saab 93 165 147
ALLISON C3	GM DEXRON® -II/IID/IIE/IIIG/IIIH	Saturn T-IV (JWS 3309)
ALLISON C-4	Honda ATF-Z1 (except in CVTs)	Scion (all vehicles)
American Motors ATF +3	Honda DW-1	Shell 3403, M115
ATF RED 1	Hyundai/Kia SP-IV/SP-IV M/SP-IV-RR/SP-III	Subaru ATF
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)	Hyundai/Kia Dex-II/ SP-II	Subaru ATF 5AT
Audi G 052 162-A1/A2	Hyundai/Kia JWS 3314/9683	Subaru DEXRON®-II
BMW JWS 3309 (T-IV)	ISUZU BESCO ATF-II/III	Subaru ATF, ATF HP
BMW LA2634	Jaguar ATF 3403 M115, ATF 3403-M115	Suzuki ATF 2326/2384K/JWS 3309/3314
BMW LT71141 (ZF 5 HP 18FL/19FL/24A)	Jaguar ATF LT71141, ZF 5HP24	Texaco 7045-E/8072B/N402
BMW ZF 5HP18FL, 5HP24, 5HP30	Jaguar JLM20238	Toyota ATF D-II/D-III/T-III/T-IV/WS
BMW 7045E	Jaguar ATF 3403 JLM20238	Volvo CE 97340
BMW ETL-8072B	JASO M315-2013 1A-LV	VW 5 HP (ZF 5 HP 30)/(18FL, 30)/(19FL, 24A)
BMW MINI	Lexus JWS 3309	VW G-055-025 A2 (JWS 3309)
CAT TO-2	KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1	VW TL 521 62
Chrysler/Dodge MOPAR AS 68 RC (T-IV), JWS 3309	Mazda ATF D-II/M-III/M-V/FZ/S-1/N-1	ZF all 3 & 4 speed transmission
Chrysler/Dodge ATF 3 & ATF 4	Mazda ATF F-1	ZF 8 & 9 speed transmission
Daewoo LT 71141	MAZDA ATF 3317	
Daihatsu AMMIX ATF D-II	MB 236.1/236.2/236.3/236.5/236.6/236.7/236.8/236.9	
Daihatsu AMMIX ATF D-III SP	MINI COOPER T-IV	
Esso LT 71141	Mitsubishi Diaqueen SK/SP-II/SP-III/SP-IV/AW/J2/J3	
FIAT T-IV type, JWS 3309	Mitsubishi Diaqueen ATF PA	
Ford MERCON® V	NAG 1 (Chrysler, Jeep, Cherokee)	
Ford FNR5/M2C138CJ/M2C166H	Nissan Matic Fluid D/J/K/S	
Ford WSS M2C 138CJ, 166H	Porsche ZF 5HP19FL, ZF 5HP20, LT71141	

For more specification information, please contact U.S. Lubricants at 1-800-490-4900.