

THRIVE Fleet HD ELC 50/50 Extended Life Premix Antifreeze/Coolant

Description

THRIVE Fleet HD ELC 50/50 is a heavy-duty antifreeze/coolant made from premium, virgin ethylene glycol for use in any diesel-powered truck, farm, off-road, marine or gasoline engine with aluminum or other engine metals.

THRIVE Fleet HD ELC 50/50 provides protection in all heavy-duty cooling systems for up to 300,000 miles or 6,000 hours when proper fluid changes take place.

THRIVE Fleet HD ELC 50/50 has a freeze protection rating of -34°F and a boiling point of 265°F when a 15 lb. pressure cap in good condition is used.

Features/Benefits

- ✓ **Free of all Phosphate, Silicate, and Borate**
- ✓ **Protects Aluminum and any other Engine Metal**
- ✓ **Fully Formulated, Extended life formulation.**

Formulated to Meet

- ✓ ASTM D6210
- ✓ ASTM D4985
- ✓ ASTM D3306
- ✓ TMC RP329
- ✓ Caterpillar EC-1

Typical Properties

Product Number	50/50 Premix
Ash Content, ASTM D1119	0.071
pH, ASTM D1287	8.7
Reserve Alkalinity, ASTM D1121	3.6
Specific Gravity @ 20°C, ASTM D1122	1.0714
Freezing Point, ASTM D1177	-34°F
Boiling Point, ASTM D1120	226°F
Foam Test, ASTM D1881	30ml/1.0 Sec
Color	Red

Cautionary Information: Ethylene glycol, the major component of Heavy Duty Antifreeze, is poisonous to humans and animals when ingested. Store only in closed containers with complete cautionary information thereon, in a cool, secure place, out of reach of children. Do not use in any system connected with potable water.