



THRIVE™ FULL SYNTHETIC UNIVERSAL ATF

Description

THRIVE™ Full Synthetic Universal ATF provides an innovative, versatile solution to virtually all your ATF needs. This advanced performance Full Synthetic ATF is specifically designed as a universal solution for modern automatic transmissions. Its state-of-the-art additive system provides optimum shear stability, oxidation resistance and durability delivering ultimate protection and peak performance in passenger cars, SUVs, and light trucks.

THRIVE™ Full Synthetic Universal ATF meets the strictest OEM specifications in low and high viscosity applications and is recommended where the following specifications are required: DEXRON VI, DEXRON III/III(H)/IIE, DEXRON II, MERCON LV, Hyundai/KIA SP-II/III/IV, Toyota WS/T-III/T-IV, Mercedes, Honda Z-1, Allison and Nissan Matic Fluids. Our fluid is also suitable for use in MERCON V specifications. See table on reverse side for a comprehensive listing of 'suitable for use in' applications.

THRIVE™ Full Synthetic Universal ATF is compatible with traditional fluids whether used in a complete fluid change or vehicle top-off.

*** Not for use in extended drain heavy duty, Continuous Variable Transmissions (CVT), Dual Clutch Transmissions (DCT) or Ford Type F applications.**

*** Please note that legislation in California prohibits recommending this fluid in certain applications where the viscometrics do not match those of the official OEM specification. Therefore we do not recommend the use of THRIVE Universal ATF in these applications in California.**



Features/Benefits

- ✓ **Universal ATF**
Simplifies and consolidates inventories, reduces inventory investment
- ✓ **Excellent Oxidation Stability**
Superior and longer lasting high temperature protection, less sludge and improved wear protection
- ✓ **High Shear Stability**
Retains its excellent friction characteristics longer and across a wide temperature range providing smooth shifting and wear protection over extended service intervals
- ✓ **Improved protection against pitting**
- ✓ **Lower Foaming**

Typical Properties

| | |
|--|------------|
| Product Number | 298 |
| Kinematic Viscosity D-445 @ 40°C, cSt | 29.1 |
| Kinematic Viscosity D-445 @ 100°C, cSt | 5.9 |
| Viscosity Index | 153 |
| Brookfield Viscosity D-2893 cPat -40°C | 10,000 |
| Appearance | Red |



THRIVE™ FULL SYNTHETIC UNIVERSAL ATF

Suitable for use in the following applications:

| | | |
|--|---|---|
| GM Dexron® -VI | Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309 | Opel (all vehicles) |
| Ford MERCON® LV | Fuso ATF-II/SPIII/A4 | Peugeot ZF 4HP20 |
| Acura ATF-Z1 | GM9986195 (Aisin AW, JWS 3309) | Porsche ZF 5HP19FL, ZF 5HP20, LT71141 |
| AISIN WARNER JWS 3309, JWS 3324, T IV, AW-1 | GM TASA | Porsche ATF 3403-M115 |
| ALLISON C3 | GM DEXRON® -II/IID/IIE/IIIG/IIIH | Porsche T-IV (JWS 3309) |
| ALLISON C-4 | Hino Blue Ribbon ATF | Saab T-IV (JWS 3309) |
| American Motors ATF +3/+4 | Honda ATF-Z1 (except in CVTs) | Saab 93 165 147 |
| ATF RED 1 | Honda DW-1 | Saturn T-IV (JWS 3309) |
| Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A) | Hyundai/Kia SP-IV/SP-IV M/SP-IV-RR/SP-III | Scion (all vehicles) |
| Audi G 052 162-A1/A2 | Hyundai/Kia Dex-II/ SP-II | Shell 3403, M115 |
| BMW JWS 3309 (T-IV) | Hyundai/Kia JWS 3314/9683 | Subaru ATF |
| BMW LA2634 | ISUZU BESCO ATF-II/III | Subaru ATF 5AT |
| BMW LT71141 (ZF 5 HP 18FL/19FL/24A) | Jaguar ATF 3403 M115, ATF 3403-M115 | Subaru DEXRON®-II |
| BMW ZF 5HP18FL, 5HP24, 5HP30 | Jaguar ATF LT71141, ZF 5HP24 | Subaru ATF, ATF HP |
| BMW 7045E | Jaguar JLM20238 | Suzuki AT OIL 5D06 |
| BMW ETL-8072B | Jaguar ATF 3403 JLM20238 | Suzuki ATF 2326/2384K/JWS 3309/3314 |
| BMW MINI | JASO M315-2013 1A-LV | Texaco 7045-E/8072B/N402 |
| CAT TO-2 | Lexus JWS 3309 | Toyota ATF D-II/D-III/T-III/T-IV/WS |
| Chrysler/Dodge MOPAR AS 68 RC (T-IV), JWS 3309 | KIA ATF SP-II, SP-III, SP-IV, SP-IVM, Red 1 | Voith 55.6335.xx (G607) |
| Chrysler/Dodge ATF 3 & ATF 4 | Mazda ATF D-II/M-III/M-V/FZ/S-1/N-1 | Volvo CE 97340 |
| Daewoo LT 71141 | Mazda ATF F-1 | VW 5 HP (ZF 5 HP 30)/(18FL, 30)/(19FL, 24A) |
| Daihatsu AMMIX ATF D-II | MAZDA ATF 3317 | VW G-055-025 A2 (JWS 3309) |
| Daihatsu AMMIX ATF D-III SP | MB 236.1/236.2/236.3/236.5/236.6/236.7/236.8/236.9 | VW TL 521 62 |
| Esso LT 71141 | MINI COOPER T-IV | ZF all 3 & 4 speed transmission |
| FIAT T-IV type, JWS 3309 | Mitsubishi Diaqueen SK/SP-II/SP-III/SP-IV/AW/J2/J3 | ZF TE-ML 09/11A |
| Ford MERCON® V | Mitsubishi Diaqueen ATF PA | |
| Ford FNR5/M2C138CJ/M2C166H | NAG 1 (Chrysler, Jeep, Cherokee) | |
| Ford WSS M2C 138CJ, 166H | Nissan Matic Fluid D/J/K/S | |

For more specification information, please contact U.S. Lubricants at 1-800-490-4900.