



THRIVE™ High Mileage Engine Oils

Description

THRIVE™ High Mileage Engine Oils use an advanced passenger car motor oil technology designed to meet the needs of higher mileage vehicles. They are formulated with the highest quality base oils combined with modern performance additives, including seal conditioners, to help prevent leaks.

THRIVE™ High Mileage Engine Oils are formulated using a special viscosity index improver which provides excellent low temperature pumpability during the life of the oil.

THRIVE™ Engine Oils exceed the industry engine performance requirements for the API Engine Oil Licensing and Certification System (EOLCS). This includes industry standards API SN and ILSAC GF-5.

Thrive™
Premium Motor Oil
The Thrive Formula
Engine Health Advantage



Features/Benefits

- ✓ **Advanced Cleaning Action**
Cleans sludge and dirt deposits off surfaces for peak running condition
- ✓ **Advanced Wear Protection**
Coats metal surfaces to minimize friction and keep metal surfaces like new
- ✓ **Advanced Heat Protection**
Anti-oxidants help maintain oil efficacy even under extreme heat
- ✓ **Advanced Viscosity Control**
Fights viscosity breakdown for optimal lubricant circulation and performance
- ✓ **Advanced Emission Control**
Helps minimize emissions for a cleaner environment
- ✓ **Incredible Warranty**
10-year/300,000 mile warranty program to attract new business and build loyalty
- ✓ **Exceptional Value**
Premium quality product without the national brand price

THRIVE™ High Mileage Engine Oils

Applications

THRIVE™ High Mileage Engine Oils meet the API requirements for SN and ILSAC GF-5. They are recommended for higher mileage (generally more than 75,000 miles) gasoline fueled automobiles and light duty trucks requiring an API SN, SM, SL or SJ product.

Performance Properties

Product Number	Viscosity Grade	Industry Performance Standards
016	10W-30	GF-5, SN, Chrysler MS-6395S
015	5W-30	GF-5, SN, Ford WSS-M2C946-A, Chrysler MS-6395S

Typical Physical and Chemical Specifications

Property	High Mileage 10W-30	High Mileage 5W-30
API Gravity @ 60°F	29.9	32.1
Viscosity @ 100°C, cSt	10.5	10.5
CCS Viscosity @ -30°C, cP	NR	< 6600
CCS Viscosity @ -25°C, cP	< 7000	NR
MRV - TP1 Pass @ °C	< -30	< -35
Phosphorus % wt.	0.077	0.077
Zinc % wt.	0.085	0.085

For Complete Engine Health™

For more information, visit www.uslube.com or call 800-490-4900.