

Aquaglide 212

Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name

Aquaglide 212

Product Number

4212A

Material Uses

Water Based Cutting and Grinding Coolant

Supplier/Manufacturer

U.S. Lubricants
A Division of U.S. Venture, Inc.
425 Better Way
Appleton, WI 54915
Phone: 920.735.8298

In Case of Emergency

920.735.8298

CAS Registry Number Not applicable for mixtures

Chemical Family Petroleum hydrocarbon

Preparation/Revision Date 02/15/04

Section 2. COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Components | CAS # | OSHA Pel | ACGIH TLV | % |
|-----------------------|------------|----------|-----------|---|
| Petroleum Hydrocarbon | 64742-54-7 | NA | NA | |

Section 3. HAZARDS IDENTIFICATION

Principal Hazard(s):

- No flash point– Product contains water.
- Contains petroleum oil.
- Avoid breathing mists or vapors.
- Avoid prolonged or repeated skin contact.

Section 4. FIRST AID MEASURES

Oral: DO NOT induce vomiting. Get immediate medical attention

Eye: Flush eye(s) with water for at least 15 minutes or until irritation subsides. Get medical attention if eye irritation develops or persists

Skin: Wash with soap and water. Immediately remove contaminated clothing. Get medical attention if irritation develops. Launder contaminated clothing before re-use. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

Inhalation: Vapor pressure is very low. Vapor inhalation under ambient conditions is normally not a problem. If adverse effects are observed, remove exposed person to fresh air. If breathing is labored,

administer oxygen. If breathing has stopped, apply artificial respiration. If overexposed to oil mist, remove from further exposure until excessive oil mist subsides.

Section 5. FIRE FIGHTING MEASURES

Flash Point: 350 degrees F

Upper Flammable Limit: Not Determined

Lower Flammable Limit: Not Determined

Extinguishing Media: Dry chemical, water spray (fog) and foam. Note: water, water fog and foam may cause frothing and spattering.

Special Firefighting Procedures: Wear self-contained breathing apparatus. Avoid breathing fumes and vapors. Use water spray (fog) to cool containers exposed to high heat or open flames,

Unusual Fire and Explosion Hazards:

Empty containers contain residue and/or vapors. DO NOT WELD, CUT, PRESSURIZE, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, SPARKS, FLAME, STATIC ELECTRICITY OR OTHER SUCH SOURCES OF IGNITION. Keep empty containers closed and dispose of in an environmentally safe manner and in accordance with all government regulations.

Auto-ignition Temperature: >600 F

Section 6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Evacuate all non-essential personal. Personal Protective Equipment must be worn (see Personal Protection Section for PPE recommendations). Remove sources of ignition. Ventilate spill area. Prevent entry into sewers and waterways. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Assure conformity with applicable Federal, state and local regulations.

Section 7. HANDLING AND STORAGE

Handling Procedures: Keep away from potential sources of ignition. Avoid breathing vapors if present. Keep containers closed when not in use. Wash thoroughly after handling. Make sure that proper warning labels are affixed in accordance with 29 CFR 1910.1200. Use good personal hygiene around product. Do not smoke or eat around product.

Storage Procedures: Do not store near potential sources of ignition. Store in a well ventilated area. Store in a dry area. Do not store around food or eating areas.

Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Procedures: Use material in well ventilated areas only. Additional ventilation or exhaust may be required to maintain air concentrations below recommended exposure limits.

Glove Protection: Use chemical resistant gloves, if needed, to avoid prolonged or repeated skin contact.

Eye Protection: Safety glasses recommended. Use splash goggles or face shield when eye contact may occur.

Respiratory Protection: Under normal conditions, respirator is not usually required. Use NIOSH/MSHA approved disposable dust/mist mask if the recommended exposure limit is exceeded.

Clothing Recommendation: Use a chemical resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Pale liquid
Specific Gravity: 1.01
Viscosity: Not Determined
Odor: Slight amine odor
Ph: 9.0-9.4
Odor Threshold: Not Determined
Water Solubility: Complete

Vapor Pressure: NA
Vapor Density (Air = 1): NA
Evaporation Rate: Not Determined
Pour or Melting Point: Not Determined
Boiling Point: Contains water. 212 °F
Percent Volatile: NA
Molecular Weight: Not Determined

Section 10. STABILITY AND REACTIVITY

Stability: Material is normally stable at room temperature and pressure. See the **Handling and Storage Section** for further details.

Incompatibility: Strong oxidizing agents.

Hazardous Polymerization: Will not occur.

Thermal Decomposition: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

Section 11. TOXICOLOGICAL INFORMATION

Oral Toxicity: Not Determined.

Eye Irritation: Product contacting eyes may cause eye irritation.

Skin Irritation: May cause skin irritation. Prolonged or repeated contact may cause dermatitis. Symptoms may include redness, edema, drying, defatting and cracking of skin.

Dermal Toxicity: Not Determined.

Inhalation Toxicity: Not Determined.

Respiratory Irritation: If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract.

Dermal Sensitivity: No data available to indicate product or components may be skin sensitizer.

Inhalation Sensitivity: No data given to indicate product or components may be respiratory sensitizer.

Chronic Toxicity: Not Determined.

Carcinogenicity: The components of this product has not been found to be a carcinogen under either NTP, IARC Monographs or current OSHA regulations.

Other: Under conditions which may generate mists, observe the OSHA PEL 5 mg/m³.

Section 12. ECOLOGICAL INFORMATION

No Data Given.

Section 13. TRANSPORTATION INFORMATION

U. S. DOT Shipping Name: Not regulated by DOT

Hazard Class: Not applicable

DOT Identification Number: Not applicable

DOT Shipping Label: Not regulated by DOT

Section 14. WASTE DIPOSAL INFORMATION

WASTE DISPOSAL: This product is not considered a hazardous waste under RCRA regulations. After use, it is the responsibility of the user to determine the products status for disposal. This product can be incinerated, if practical, or recycled.

Section 15. REGULATORY INFORMATION

U. S. TSCA Inventory: All components of this product are listed on the TSCA Inventory.

SARA 302 Threshold Planning Quantity: No RQ for product or any constituent greater than 1.0% or 0.1% (carcinogen).

SARA 304 Reportable Qty: No RQ for product or any constituent greater than 1.0% or 0.1% carcinogen).

SARA 311 Categories: EPA Hazard Classification Code

| Acute | Chronic | Fire | Pressure | Reactivity |
|-------|---------|------|----------|------------|
| No | No | No | No | No |

SARA 313 Supplier Notification:

This product does not contain greater than 1.0% (greater than 0.1% for carcinogenic substances) of any chemical substances listed under SARA Section 313.

CERCLA Hazardous Substances:

No chemicals in this product are subject to the reporting requirements of CERCLA.

Section 16. OTHER INFORMATION

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)

HEALTH = 1 FIRE = 1 REACTIVITY = 0 PP = B

Rating: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Extreme

Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, **U.S. Venture, Inc.** makes no representations as to the completeness or accuracy thereof. **U.S. Venture, Inc.** makes no warranty whatsoever, expressed or implied, of **MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE** since the conditions of use are beyond our control. **U.S. Venture, Inc.** assumes no responsibility for injury to recipient or to third persons for any damage to any property and recipient.