



150 SUPER CYLINDER OIL Premium Steam Cylinder Oil

Description

150 Super Cylinder Oil is a blend of high quality base stocks and lubricity additives. Specifically formulated for Steam Cylinder lubrication, it can also be used for lubrication of slow speed industrial gear applications, worm drives and slow speed loaded journal bearings.

150 Super Cylinder Oil is formulated to withstand higher temperatures with excellent resistance to thermal degradation. This product protects against rust and corrosion, provides good sealing film strength, excellent lubricity and is resistant to water washout.

Features/Benefits

- ✓ **Excellent Wear Protection.**
- ✓ **Ready Separation from Condensate.**
- ✓ **Resistant to Deposit Formation at High Temperatures**

150 Super Cylinder Oil is recommended for low pressure saturated steam systems. It may also be used for couplings, bearings, splash-lubricated worm gear sets operating at moderate to high speeds and temperatures and for the break-in of compressor cylinders.

Physical & Chemical Properties

Product Code	158
ISO Viscosity Grade	320
AGMA Grade	6
API Gravity	27.1
Density lb/gal	7.43
Viscosity @ 40°C, cSt	350
Viscosity @ 100°C, cSt	25.5
Viscosity @ 104°F, SUS	1620
Viscosity @ 212°F, SUS	122
Viscosity Index	95
Pour Point, °F, typ.	20
Flash Point, °F, ASTM D 92	400
Copper Corrosion ASTM D 130	1a