

Zinc Free Hi VI Multi-Vis 32 Hydraulic Oil

Description

Zinc Free Hi VI Multi-Vis 32 Hydraulic Oil is a premium high VI hydraulic fluid designed for year round service. It is formulated with a non-zinc ashless anti-wear additive to provide environmental benefits and significant performance and reliability advantages.

Zinc Free Hi VI Multi-Vis 32 Hydraulic Oil combines this unique anti-wear package with superior Group II base oils. The use Group II base stocks in this product typically increase the D 943 oxidation performance to exceed 5000 hours.

Zinc Free Hi VI Multi-Vis 32 has superior oxidation stability and resists breakdown at high temperatures. It provides excellent anti-wear protection, filterability, and demulsibility.

Reduced fish toxicity versus zinc containing products. Ideal where disposal of oils containing heavy metals is a concern

Features/Benefits

- ✓ **Environmentally Friendly**
- ✓ **High Viscosity Index VI**
- ✓ **Exceptional Anti-wear Protection**
- ✓ **Excellent Low Temperature Properties**
- ✓ **Reduced Effluent Treatment Costs Proven Field Performance**
- ✓ **Excellent Water Separation**
- ✓ **Superior Thermal Stability**

Applications

Zinc Free Hi VI Multi-Vis 32 Hydraulic Oil has been developed to meet or exceed the requirements of all conventional and high-output industrial and mobile hydraulic systems.

Typical Properties

Product	Zinc Free Hi VI Multi-Vis 32
°API Gravity @ 60°F	32.3
Viscosity @ 40° C, cSt	32
Viscosity @ 100° C, cSt	6.6
Viscosity Index, typ	165
Pour Point °F, typ	-50
DIN 51524 Part 3	HVLP 32
ISO Grade	32