

AQUAGLIDE™ 410 Medium Duty Multi-Purpose Soluble Oil Metalworking Coolant

Description

Aquaglide™ 410 is a medium-duty water-soluble coolant designed for use on ferrous and non-ferrous metals.

Aquaglide™ 410 can be used for grinding, sawing, tapping, milling, and drilling.

Aquaglide™ 410 is low foaming to prevent sump over flow and pump cavitation.

Aquaglide™ 410 contains exceptional biocide packages that both resist bacteria & fungus growth and eliminate the rotten egg smell associated with bacteria growth.

Aquaglide™ 410 provides good interim protection on parts and equipment and is very operator friendly eliminating skin irritation concerns.

Refractive Index

Concentration Percent	Dilution Ratio	Refractometer Reading
6%	16:1	6.6
7%	14:1	7.7
8%	12:1	8.8
9%	11:1	9.9
10%	10:1	11

Application Information

Application Type	Concentration	
General Machining	6 - 10%	
Consult with your U.S. Lubricants Specialist for application-specific recommendations		

Features/Benefits

- √ In Process RP
- √ Insures Quality Part Finish
- ✓ Imparts Excellent Tool Life
- ✓ Versatile

Typical Properties

Property	Results
Appearance	Amber/Green
Appearance of	Milky White
5% Dilution	Emulsion
Odor	Low
pH (@5%)	8.6
Chlorine	Yes
Sulfur	No

