

AQUAGLIDE™ 450 Heavy Duty Soluble Oil Metalworking Coolant

Description

Aquaglide™ 450 is a heavy-duty water-soluble coolant designed for use in tough operations on steel and aluminum alloys. It is effective in turning, tapping, milling, drilling, sawing and medium-duty forming operations.

Aquaglide™ 450 is designed to produce low foam in high agitation situations, consequently preventing sump over flow and pump cavitation.

Aquaglide™ 450 contains exceptional biocide packages that both resist bacteria & fungus growth and eliminate the rotten egg smell associated with bacteria growth.

Refractive Index

Concentration Percent	Dilution Ratio	Refractometer Reading
4%	25:1	4.4
5%	20:1	5.5
6%	16:1	6.6
7%	14:1	7.7
8%	12:1	8.8
9%	11:1	9.9
10%	10:1	11

Application Information

Application Type	Concentration	
Heavy Duty Machining	8 - 10%	
Moderate Machining	5 – 7%	
Consult with your U.S. Lubricants Specialist for application-specific recommendations		

Features/Benefits

- √ In Process RP
- ✓ Insures Quality Part Finish
- **Imparts Excellent Tool Life**
- ✓ Low-Foaming in High **Agitation**
- ✓ Versatile for Multiple **Operations**
- √ Good Operator Acceptance

Typical Properties

Property	Results
Appearance	Green
Appearcance	Milky Green
(Diluted)	Emulsion
pH (@5%)	8.6
Odor	Low
Chlorine	Present

