

Global Automotive Extended Life ANTIFREEZE/COOLANT

Global Automotive Extended Life Antifreeze/Coolant is a premium quality, virgin ethylene glycol-based, organic acid technology (OAT) fluid. It is specially formulated with industry-leading additives to provide optimum performance in all makes and all models of cars and light duty trucks.

- Designed for automotive use in model years 1996 and newer
- Provides up to 5 years or 150,000 miles of protection
- Compatible with other organic acid technology (OAT) coolants, regardless of color
- Meets or exceeds ASTM D3306 and SAE J1034 specifications



THRIVE® Global Automotive Extended Life Antifreeze/Coolant is your cooling system's best defense.

- Premium quality, extended life coolant made from virgin ethylene glycol
- User-friendly color does not change the color of the coolant already in the reservoir
- Provides freeze and boil-over protection
- Free of phosphates, borates, nitrites, silicates, and amines
- Protects against corrosion of all cooling system metals, including aluminum
- High-quality defoamer system, non-harmful to hoses, plastics or gaskets
- Not recommended for use in heavy duty applications

Consult your vehicle's owner's manual for recommendations.

Available in:

CONCENTRATE	50/50 PREMIX
Bulk #809100	NA
55G Drum #855100	55G Drum #8558100
3X1G Case #803100	3X1G Case #8038100

TECHNICAL INFORMATION	CONCENTRATE	50/50
Fluid Color	Yellow	Yellow
Density @ 68°F, lb/gal	9.3	8.9
pH (50v% solution)	8.1	8.1
Coolant Lifetime, miles (years)	150,000 (5)	150,000 (5)

Freeze/Boil Protection

% Cooling System Capacity	PROTECTION FROM	
	Freezing Down to	Boiling Up To†
40	-13°	+260°F
50	-34°	+265°F
60	-62°	+270°F

†Using a 15 psi pressure cap

Recommended for use in:

- | | |
|-----------------------|--------------------------|
| ASTM D3306 | GM 6277M (DEX-COOL®**) |
| ASTM D4985* | GMW 3420 |
| Chrysler MS-12106 | John Deere JDM H24C1, C2 |
| Chrysler MS-90032 | John Deere JDS-G135 LD |
| Ford WSS-M97B44-D/D2 | SAE J1034 |
| Ford WSS-M97B44-E1/E2 | VW TL774-C/F |
| Ford WSS-M97B51-A1 | |
| Ford WSS-M97B55-A | |

*Meets performance requirements—chemical requirements not applicable to OAT coolants. Always consult your vehicle's owner's manual for proper fluid removal and flushing procedures. **DEX-COOL is a registered trademark of the General Motors Corporation®.