

## For Vehicles Requiring DEX-COOL® ANTIFREEZE/COOLANT

Antifreeze/Coolant for vehicles requiring DEX-COOL® is a premium Organic Acid Technology (OAT), virgin ethylene glycol-based fluid. Specially formulated with industry-leading additives, this product provides optimum performance in vehicles requiring DEX-COOL® (GM 6277M or GMW 3420) coolant.

- Provides up to 5 years or 150,000 miles of protection
- Full Organic Acid Technology (OAT)
- Helps prevent freeze-ups and boil-overs
- Meets or exceeds ASTM D3306 and SAE J1043 specifications



### THRIVE® For Vehicles requiring DEX-COOL® Antifreeze/Coolant is your cooling system's best defense.

- Premium quality, extended life coolant
- Free of phosphates, borates, nitrites, silicates, and amines
- Protects against corrosion of all cooling system metals, including aluminum
- Provides freeze and boil-over protection
- High-quality defoamer system, non-harmful to hoses, plastics or gaskets
- Formulated for use in newer Chrysler® (2013 and later), Ford® (2011 and later), and GM® (1996 and later) vehicles requiring an orange OAT coolant
- Compatible with major American brands of extended life Organic Acid Technology type antifreeze/coolant formulated to meet the DEX-COOL® requirement (GM 6277M or GMW 3420)

*\*DEX-COOL® is a registered trademark of the General Motors Corporation\*. Consult your vehicle's owner's manual for recommendations. Chrysler®, Ford®, and GM® are registered trademarks of their respective corporations.*

**Available in:**

CONCENTRATE	50/50 PREMIX
55G Drum #855300	55G Drum #8558300
3X1G Case #803300	3X1G Case #8038300

TECHNICAL INFORMATION	CONCENTRATE	50/50
Fluid Color	Orange	Orange
Density @ 68°F, lb/gal	9.3	8.9
pH (50v% solution)	8.1	8.1
Coolant Lifetime, miles (years)	150,000 (5)	150,000 (5)

**Freeze/Boil Protection**

% Cooling System Capacity	PROTECTION FROM	
	Freezing Down to	Boiling Up To†
40	-13°	+260°F
50	-34°	+265°F
60	-62°	+270°F

†Using a 15 psi pressure cap

**Recommended for use in:**

ASTM D3306	Ford WSS-M97B55-A
ASTM D4985*	GM 6277M (DEX-COOL®)**
Chrysler MS-12106	GMW 3420
Chrysler MS-90032	John Deere JDM H24C
Ford WSS-M97B44-D/D2	John Deere JDS-G135
Ford WSS-M97B44-E1/E2	SAE J1034
Ford WSS-M97B51-A1	VW TL774-C/F

*\*Meets performance requirements; chemical requirements not applicable to OAT coolants. Always consult your vehicle's owner's manual for proper fluid removal and flushing procedures. \*\*DEX-COOL® is a registered trademark of the General Motors Corporation\*. Chrysler®, Ford®, GM®, John Deere®, and Volkswagen® are registered trademarks of their respective corporations.*