

Heavy Duty Precharged Green ANTIFREEZE/COOLANT

THRIVE® Heavy Duty Pre-Charged Antifreeze/Coolant is a premium quality conventional technology, virgin ethylene glycol-based fluid. Specially formulated with additive technology designed to protect heavy duty engines, this product provides protection without an initial charge of SCAs. Meets conventional coolant requirements of most industry-leading OEMs.

- No initial charge of SCAs required—use THRIVE® SCA to maintain fluid at recommended maintenance intervals
- Amine free with low silicate
- Meets or exceeds: ASTM D3306, ASTM D6210, TMC RP329
- Service life of 300,000 miles | 6,000 hours of offroad use*

*Fluid must be maintained using THRIVE® SCA approximately every 30,000 miles. Consult your vehicle's owner's manual for recommendations.



THRIVE® Heavy Duty Pre-Charged Antifreeze/Coolant is your cooling system's best defense.

- Contains nitrites for wet sleeve liner cavitation protection
- Provides maximum freeze and boil-over protection
- Corrosion protection for steel, solder, copper, iron, brass and aluminum
- High-quality defoamer system, non-harmful to hoses, plastics or gaskets
- Compatible with all major American brands of conventional coolants
- Ideal for older Cummins, Detroit Diesel, Navistar, John Deere, or mixed fleets—see list of specifications for additional applications

Available in:

CONCENTRATE	50/50 PREMIX	TECHNICAL INFORMATION	CONCENTRATE	50/50
55G Drums #855600	55G Drums #8558600	Fluid Color	Green	Green
		Density @ 68°F, lb/gal	9.3	8.9
		pH (50v% solution)	10.5	10.5
		Maintenance Interval, miles (hours)	30,000 (600)	30,000 (600)
		Coolant Lifetime, miles (hours)	300,000 (6,000)	300,000 (6,000)

Freeze/Boil Protection

% Cooling System Capacity	PROTECTION FROM	
	Freezing Down to	Boiling Up To†
40	-13°	+260°F
50	-34°	+265°F
60	-62°	+270°F

†Using a 15 psi pressure cap

Recommended for use in:

- | | |
|---|--|
| ASTM D3306
ASTM D6210
BS 6580:2010
Buhler Versatile 86050054
CAT DEAC
CAT EC-1
CID-A-52624A
CNH MAT 3620 EG3, EG4
Cummins CES 14439
Cummins CES 14603
Daimler DBL 7700
Detroit Diesel 7SE298 | Deutz H 0685-6: Class DQC CA-14
Ford ESE-M97B18-C
JCB STD00088
John Deere JDM H24A1, A2
MAN 324 Type N
MWM Deutz TR0199-99-2091
Navistar CEMS B-1 Type II
Navistar MPAPS B-1 Type II
Perkins (CAT) SEBU7833-03
TMC RP 329
Volvo Coolant Requirements: Volvo Trucks |
|---|--|

Always consult your vehicle's owner's manual for proper fluid removal and flushing procedures.