

product data sheet

THRIVE[™] ECO Lubricants 2-Cycle Engine Oil Renewable / Biodegradable

Description

THRIVE™ Eco 2-Cycle Engine Oil is formulated from proprietary renewably-sourced synthetic base oils and an optimized additive system. It provides the maximum level of performance and protection while vastly reducing environmental impact.

THRIVE™ Eco 2-Cycle Engine Oil contains an advanced, low ash additive package that enables it to meet or exceed OEM equipment specifications while maintaining excellent environmental characteristics including renewability, low toxicity and low smoke operation.

THRIVE™ Eco 2-Cycle Engine Oil is suitable for applications including direct injection or premix and most air-cooled engines.

Typical Properties

Properties	2-Cycle Engine Oil
Product Number	
Viscosity @ 40°C, cSt	60.25
Viscosity @ 100°C, cSt	9.46
Viscosity Index, typ	139
Specific Gravity @ 15°C (g/mL)	.84
Pour Point, °C	-33
Flash Point, °C	125
Sulfated Ash, Mass %	.05
Color	Blue

THRIVE[™], THRIVE[™] and ring mark, and U.S. and star are trademarks of U.S. Venture, Inc. 425 Better Way, Appleton, WI 54915 www.uslube.com ● 800.490.4900

Features/Benefits

- ✓ Low Smoke Operation Reduces smoke and odor associated with two-cycle engines.
- Superior Lubricity
 Controls cylinder, piston, bearing wear and reduces ring sticking.
- Low Pour Point
 High performance in very cold environments.
- Optimized Viscosity
 Improved system performance over a wide temperature range.
- Excellent Anti-Wear Protection Prevents corrosion and carbon deposits.
- High Purity Renewably-Sourced Synthetic Base Oils Reduces dependence on petroleum.
- Low Toxicity Reduces environmental impact in case of leaks or spills.

Meets or Exceeds:

- ✓ API-TC
- ✓ JASO-FD
- ✓ ISO-L-EGD
- ✓ SAE GRADE

