



SYNTHETIC LONG DRAIN Commercial ATF TES-295

Description

Synthetic Long Drain Commercial ATF is a premium quality PAO synthetic fluid designed for use in commercial automatic transmissions.

While **Synthetic Long Drain Commercial ATF** is not licensed by transmission manufacturers, it is designed for use according to the drain recommendations of the transmission manufacturer for the listed specifications.

Synthetic Long Drain Commercial ATF utilized premium base oil and additives that provide for extended drain intervals and worry free service.

Physical, Chemical & Performance Properties

Product Number	200
Viscosity @ 100°C cSt	7.5
Viscosity @ 40°C cSt	36.6
Viscosity Index	179
Density (lb/gal)	6.968
Brookfield Viscosity (-40°C) cP	8475
Foam Tendency	0/0/0
Copper Corrosion	1b
Pour Point °C (°F)	-54 (-65)

Features/Benefits

- ✓ **Excellent Thermal and Oxidative Stability for Long Transmission Life**
- ✓ **Exceptional All-weather Performance in Both Hot and Cold Temperature Extremes.**
- ✓ **Durable Friction Properties Ensure Smoother Shifting Transitions**
- ✓ **Shear Stable for Long Term Viscosity Protection**

Applications

Formulated for use in applications according to the listed performance specification:

- ✓ **Allison TES-295 & TES-389, C-4**
- ✓ **GM Dexron® III-H**
- ✓ **Ford Mercon® V**
- ✓ **MAN 339 Type V-1, V-2, Z-1, Z-2, Z-3, MAN 339F**
- ✓ **MB 236.91, 236.10**
- ✓ **Voith 55.6335, 55.6336**
- ✓ **Volvo 97340**
- ✓ **Volvo 97341**
- ✓ **ZF TE-ML 03D, 04D, 14A, 14B, 14C, 17C, 20B, 20C**