

## THRIVE FG Can Seam Food Grade Can Seaming Oils

### Description

**THRIVE FG Can Seam ISO 150 OT** is designed for lubricating the gears on food canning equipment that utilize a "once through" lubrication style, that allows the oil to drain out of the system after one pass over the gears.

**THRIVE FG Can Seam ISO 150 RS** is formulated for food canning equipment that reuses oil rather than dumping after one pass.

**THRIVE FG Can Seam ISO 150 RS** allows for optimum particulate filterability and liquid separation.

**THRIVE FG Can Seam Oils** are registered Food Grade, Category H1 with NSF and are listed in the NSF white book. This registration make **THRIVE FG Can Seam Oils** excellent choices in any situation where food grade lubrication is required in case of incidental food contact.

*Meets USDA 1998 (H1) guidelines for lubricants with incidental food contact.*

### Features/Benefits

- ✓ **Superior Rust and Corrosion Protection**
- ✓ **Enhanced AW and EP Additives**
- ✓ **Exceptional Water Separation**
- ✓ **Resists Foaming in Service**
- ✓ **Free of Heavy Metals**

### Typical Properties

Properties	OT	RS
ISO Grade	150	150
Viscosity @ 40°C, cSt	146	154.7
Viscosity @ 100°C, cSt	14.5	19.2
Pour Point °F	0	-49
FZG Gear Test	12+ Pass	N/A
NSF Registration Number (Category Code: H1)	156580	156581