

SYN 5W40 HP EURO High Performance Synthetic SAE 5W40 Engine Oil

Description

SYN 5W40 HP EURO is a full synthetic gasoline and light duty diesel engine oil engineered for high performance European automobiles including Mercedes Benz, Volkswagen, BMW and Porsche.

SYN 5W40 HP EURO is a unique blend of full sulfated ash, phosphorus and sulfur (SAPS) for long-term engine protection.

Physical, Chemical & Performance Properties

Properties	ASTM	Results
Product Number		016
SAE Grade		5W-40
Kinematic Viscosity		
At 100°C, cSt	D 445	13.5
At 40°C	D 445	83.1
Viscosity Index	D 2270	166
Cold Crank Simulator, cP	D 5293	5460 (-30°C)
Flash Point, °C (°F) (COC)	D 92	218(424)
Fire Point, °C (°F) (COC)	D 92	238 (460)
Pour Point, °C (°F) (COC)	D 97	-38 (-36)
NOACK (%wt loss)	D 5800	8.9%
Four Ball Wear Test 75°C, 1200rpm, 40kg, 1 hr	D 4172	0.48
Total Base Number (TBN)	D 2896	10.0
HTHS (cP)	D 4683	3.7

Features/Benefits

- ✓ Excellent Heat Resistance and Cold Temperature Performance
- ✓ Highly Active Zinc/Phosporus delivers Excellent Wear Protection
- ✓ High Dispersant/Detergent
 Content Maintains Very Clean
 Engines
- ✓ Meets Long Life Requirements
 of OFMs
- ✓ Compatible with Conventional and Synthetic Oil

Applications

SYN 5W40 HP EURO is designed to meet the following Industry and OEM specifications.

OEM Specification	
ACEA A3/B3, A3/B4	✓
API SN, SM	✓
BMW LL-01	✓
Mercedes Benz 229.3/229.5	√
Porsche A40	✓
OPEL GM-LL-B-025	✓
Renault 0710, 0700	√
Volkswagen 502.00/505.00	√

