

Global Automotive Extended Life ANTIFREEZE/COOLANT

Global Automotive Extended Life Antifreeze/Coolant is a premium quality, ethylene glycol-based, organic acid technology (OAT) fluid. It is specially formulated with industry-leading additives to provide optimum performance in all makes and all models of cars and light duty trucks.

- Designed for automotive use in model years 1996 and newer
- Provides up to 5 years or 150,000 miles of protection*
- Compatible with other organic acid technology (OAT) coolants, regardless of color
- Suitable for use in applications calling for: ASTM D3306
- Meets ASTM D6472 and ASTM D6471 **With proper maintenance and top off*



THRIVE® Global Automotive Extended Life Antifreeze/Coolant is your cooling system's best defense.

- Premium quality, extended life coolant made from ethylene glycol
- User-friendly color does not change the color of the coolant already in the reservoir
- Provides freeze and boil-over protection
- Protects against corrosion of all cooling system metals, including aluminum
- High-quality defoamer system, non-harmful to hoses, plastics or gaskets
- Not recommended for use in heavy duty applications

Consult your vehicle's owner's manual for recommendations.

Available in:

CONCENTRATE		50/50 PREMIX		TECHNICAL INFORMATION	CONCENTRATE	50/50
Bulk #809100	Bulk	Bulk		Fluid Color	Yellow	Yellow
275G Tote	275G Tote	275G Tote		Density @ 68°F, lb/gal	9.3	8.9
55G Drum #855100	55G Drum #8558100	55G Drum #8558100		pH (50v% solution)	8.6	8.6
6X1G Case #803100	6X1G Case #8038100	6X1G Case #8038100		Coolant Lifetime, miles (years)	150,000 (5)	150,000 (5)

Freeze/Boil Protection

% Cooling System Capacity	PROTECTION FROM	
	Freezing Down to	Boiling Up To
50	-34°F	+226°F

Recommended for use in:

ASTM D3306
 ASTM D4985
 Chrysler
 Ford
 General Motors
 ASTM D6471
 ASTM D6472

**Meets performance requirements—chemical requirements not applicable to OAT coolants. Always consult your vehicle's owner's manual for proper fluid removal and flushing procedures.*