

Premium Zinc Free Multi-Vis-FM

Hydraulic Oil ISO 15

Description

Zinc Free Multi-Vis-FM Hydraulic Oil ISO 15 is a premium quality hydraulic fluid designed around the requirements of the U.S. Military specification MIL-H-5606A (now obsolete). It is designed for use in industrial and commercial equipment requiring good oil fluidity at very low temperatures.

Zinc Free Multi-Vis-FM Hydraulic Oil ISO 15 has a very low pour point that makes it suitable for use at temperatures approaching -40°F. This unique fluid is also formulated with a friction modifier to increase lubricity and eliminate stick/slip and chatter in a variety of applications.

Zinc Free Multi-Vis-FM Hydraulic Oil ISO 15 is zinc free, making it environmentally friendly. This formulation has a long history of excellent performance and provides long, trouble-free service over a wide range of operating conditions.

Zinc Free Multi-Vis-FM Hydraulic Oil ISO 15's performance additive has been formulated to meet or exceed the requirements of all conventional and high-output industrial and mobile hydraulic systems.



Features/Benefits

- Proven Field Performance
- Friction Modified for Added Lubricity
- Enhanced Low Temperature Properties
- Excellent Thermal Stability
- Superior Anti-wear Protection
- Excellent Water Separation
- Exceptional Filterability
- Excellent Rust and Corrosion Protection
- Resists Foaming in Service
- Environmentally Friendly

Meets or Exceeds the Requirements of:

- Denison
- Vickers
- Cincinnati Milacron
- U.S. Steel

Typical applications include snow plows, bucket trucks and loading docks.

Typical Properties

Product Number	200
ISO Grade	15
API Gravity @ 60°F	29.6
Viscosity @ 40°C, cSt	15
Viscosity @ 100°C, cSt	4.6
Viscosity Index	250
Pour Point °F	-60