

## For Vehicles Requiring DEX-COOL® ANTIFREEZE/COOLANT

Antifreeze/Coolant for vehicles requiring DEX-COOL® is a premium Organic Acid Technology (OAT), ethylene glycol-based fluid. Specially formulated with industry-leading additives, this product provides optimum performance in vehicles requiring DEX-COOL® (GM 6277M or GMW 3420) coolant.

- Provides up to 5 years or 150,000 miles of protection\*
- Full Organic Acid Technology (OAT)
- Helps prevent freeze-ups and boil-overs
- Suitable for use in applications calling for: ASTM D3306 and SAE J1043 specifications

\*With proper Maintenance and top off



### THRIVE® For Vehicles requiring DEX-COOL® Antifreeze/Coolant is your cooling system's best defense.

- Premium quality, extended life coolant
- Protects against corrosion of all cooling system metals, including aluminum
- Provides freeze and boil-over protection
- High-quality defoamer system, non-harmful to hoses, plastics or gaskets
- Formulated for use in newer Chrysler® (2013 and later), Ford® (2011 and later), and GM® (1996 and later) vehicles requiring an orange OAT coolant
- Compatible with major American brands of extended life Organic Acid Technology type antifreeze/coolant formulated for vehicles calling for DEX-COOL® (GM 6277M or GMW 3420)

*\*DEX-COOL® is a registered trademark of the General Motors Corporation®. Consult your vehicle's owner's manual for recommendations. Chrysler®, Ford®, and GM® are registered trademarks of their respective corporations.*

**Available in:**

CONCENTRATE	50/50 PREMIX
55G Drum #855300	55G Drum #8558300
6X1G Case #803300	6X1G Case #8038300

TECHNICAL INFORMATION	CONCENTRATE	50/50
Fluid Color	Orange	Orange
Density @ 68°F, lb/gal	9.3	8.9
pH (50v% solution)	8.6	8.6
Coolant Lifetime, miles (years)	150,000 (5)	150,000 (5)

**Freeze/Boil Protection**

% Cooling System Capacity	PROTECTION FROM	
	Freezing Down to	Boiling Up To
50	-34°F	+226°F

**Recommended for use in:**

- ASTM D3306
- ASTM D4985
- Chrysler
- Ford
- General Motors
- ASTM D6471
- ASTM D6472

*\*Meets performance requirements; chemical requirements not applicable to OAT coolants. Always consult your vehicle's owner's manual for proper fluid removal and flushing procedures. \*\*DEX-COOL® is a registered trademark of the General Motors Corporation®, Chrysler®, Ford®, GM®, John Deere®, and Volkswagen® are registered trademarks of their respective corporations.*